# **ARIES CARTRIDGE SPECIFICATION SHEET**

# **GOLD & SILVER REMOVAL**

PRO SERIES, SINGLE-BED, DROP-IN CARTRIDGE

SILVER REMOVAL

GOLD REMOVAL

CYANIDE REMOVAL

Aries gold and silver removal cartridges use ResinTech® SBG1, a high crosslinked resin with higher ion exchange density than other strong base anion resins. Sized to fit standard slimline and big blue housings.



# **HIGHLIGHTS**

- Resintech® SBG1
- Fits Standard Residential & Industrial Size Housing
- Oversized Cartridge for Maximum Media Fill
- Lot numbered
- Made in the USA

# **APPLICATIONS**

Industrial

## **MEDIA**

• ResinTech® SBG1 (100%)

### **SPECIFICATIONS**

- Nominal Rating of 25µ
- Max Pressure of 125 psi (861.85 kpa)
- Max Temperature 100°F (37.8 °C)

DIMENSIONS	SERVICE FLOW	MAX FLOW	CAPACITY	PART NUMBER
2.5 x 10 in. (Slim Line)	.25 gpm (0.95 lpm)	.5 gpm (1.89 lpm)	850 grains	AF-10-3200
2.5 x 20 in. (Slim Line)	.5 gpm (1.89 lpm)	1 gpm (3.79 lpm)	1,500 grains	AF-20-3200
4.5 x 10 in. (Super Blue)	.5 gpm (1.89 lpm)	1 gpm (3.79 lpm)	1,500 grains	AF-10-3200-BB
4.5 x 20 in. (Super Blue)	1 gpm (3.79 lpm)	2 gpm (7.57 lpm)	4,400 grains	AF-20-3200-BB



#### COMPONENT

Filter cartridge Certified to NSF/ANSI Standard 42 and NSF/ANSI Standard 61 for material requirement(s) only. Filter cartridge Certified to NSF/ANSI Standard 372 for low lead compliance.

Revision 1.0 © 2020 ResinTech, Inc.

