HIGH PURITY COLOR CHANGING

DEIONIZATION

INLINE SERIES, MIXED BED, DROP-IN CARTRIDGE

Aries high-purity mixed bed deionization filters provide a resistivity greater than 10 M Ω . Color-changing cartridges provide for easy indication distinctively changing from blue to amber upon resin exhaustion, without the need for monitors or indicating lights. Available in Quick Connect or 1/4" FNPT connectors in 5 and 10" lengths. Aries Inline filters cartridges are designed for low-flow, point-of-use filtration.



HIGHLIGHTS

- Visually Indicates Exhaustion
- Greater than 10 Megohm Resistivity
- Fits Standard Residential & Industrial Size Housing
- Oversized Cartridge for Maximum Media Fill
- Quality Produced & Made in the USA

APPLICATIONS

- Post RO
- Spot Free
- Aquarium

MEDIA

• ResinTech® MBD-30 (100%)

SPECIFICATIONS

- Nominal Rating of 25µ
- Max Pressure of 125 psi (861.85 kpa)
- Max Temperature 100°F (37.8 °C)

| DIMENSIONS | SERVICE FLOW | MAX FLOW | CAPACTIY | PART NUMBER |
|----------------------------|--------------|----------|------------|----------------|
| 5 x 2 in. (Quick Connect) | 5 gph | 10 gph | 90 grains | IFC-05-4030-QC |
| 10 x 2 in. (Quick Connect) | 5 gph | 10 gph | 180 grains | IFC-10-4030-QC |
| 5 x 2 in. (1/4 in. FNPT) | 5 gph | 10 gph | 90 grains | IFC-05-4030-FT |
| 10 x 2 in. (1/4 in. FNPT) | 5 gph | 10 gph | 180 grains | IFC-10-4030-FT |



COMPONENT

Filter cartridge Certified to NSF/ANSI Standard 42 and NSF/ANSI Standard 61 for material requirement(s) only. Filter cartridge Certified to NSF/ANSI Standard 372 for low lead compliance.

Revision 1.0 © 2020 ResinTech, Inc.

