PX-xx-5002

(Phoenix Dual Conditioning Pack (SDI Carbon/Mix Bed)

Effective date 1 January 2021

SECTION 1: Identification	
1A: Product Names	PX-xx -5002
1B: Common Name	Phoenix Dual Conditioning Pack (SDI Carbon/ Mix Bed)
1C: Intended use	Applications where deionized water is needed with additional pretreatment.
1D: Manufacturer Address	ResinTech, Inc. 1801 Federal Street, Camden, NJ 08105 USA
Contact Information:	856-626-1550 info@resintech.com

SECTION 2: Hazard Identification	
2A: OSHA Hazard classification	Not hazardous or dangerous
0 = Negligible	Health - 1 (1 = Slight)
1 = Slight	Fire - 1 (1 = Slight)
2 = Moderate	Reactivity - 0 (0 = Negligible)
3 = High	Special - N/A
4 = Extreme	
	H315: Causes skin irritation (Category 2)
	H319: Causes serious eye irritation (Category 2A)
♦ WARNING	H320: Causes eye irritation (Category 2B)
	H335: May cause respiratory irritation (Category 3)*
	* chronic risk from breathing dust





SECTION 2: Hazard Identification Continued	
	P261: Avoid breathing dust/fume/gas/mist/vapors/spray
	P264: Wash hands thoroughly after handling.
	P280: Wear protective gloves/protective clothing/eye protection/face protection
	P284: In case of inadequate ventilation wear respiratory protection.
	P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Precautionary Statements	P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing.
	P333+313: If skin irritation or a rash occurs: Get medical advice/attention.
	P337+313: If eye irritation persists get medical advice/ attention.
	P403+233: Store in a well-ventilated place. Keep container tightly closed.
	P411: Store at temperatures not exceeding 50 °C/ 122 °F.
2B: Product description	Mix Bed - Amber, tan, dark brown, or black cation beads blended with white, yellow, orange, or red anion beads, all approx. 0.6 mm diameter. Carbon - Black irregular pieces with little or no odor.
2C: Precautions for use	Safety glasses and gloves recommended. Slipping hazard if spilled. Wet carbon adsorbs oxygen from air and can cause a hazard in confined spaces. Avoid breathing dust when handling dry carbon. Dust mask or respirator recommended for poorly ventilated spaces.
Potential health effects	Will cause eye irritation. May cause mild skin irritation. Ingestion is not likely to pose a health risk. Dust may be mildly irritating.
2D: Environmental effects	This product may alter the pH of any water that contacts it.

SECTION 3: Composition/ Information on Ingredients	
3A: Chemical name	Mix bed of polystyrene sulfonate in the hydrogen form and trimethylamine functionalized chloromethylated copolymer
	of polystyrene in the hydroxide form.



SECTION 3: Composition/ Information on Ingredients	
3B: Ingredients: Water	Mixed Bed- CAS# 7732-18-5 (40 - 70%)
	Carbon- CAS# 7732-48-5 (2 - 20%)
Polystyrene sulfonate in the hydrogen form	CAS# 69011-20-7 (10 - 30%)
Trimethylamine functionalized chloromethylated	CAS# 69011-20-7 (40 - 60%)
copolymer of polystyrene in the hydroxide form	
Granular Carbon	CAS# 7440-44-0 (80 – 88%)

SECTION 4: First Aid Measures	
4A: Inhalation	No adverse effects expected. Normal use of product does not produce odors or vapors. Carbon dust may be mildly irritating to the upper respiratory tract.
4B: Skin	Wash with soap and water- seek medical attention if a rash develops.
4C: Eye contact	Wash immediately with water-seek attention if discomfort continues.
4D: Ingestion	No adverse effects expected for small amounts, larger amounts can cause stomach irritation. Seek medical attention if discomfort occurs.

SECTION 5: Fire Fighting Measures	
5A: Flammability	NFPA Fire rating = 1
5B: Extinguishing media	Water, CO ₂ , foam, dry powder
5C: Fire fighting Procedures	Follow general fire fighting procedures indicated in the work place.
5D: Protective Equipment	MSHA/NIOSH approved self-contained breathing gear, full protective clothing.
5E: Combustion Products	Carbon oxides and other toxic gasses and vapors.
5F: Unusual Hazards	Product is not combustible until moisture is removed. Resin begins to burn at approximately 230° C. Auto ignition can occur above 500° C.



SECTION 6: Accidental Release Measures	
6A: Personal Precautions	Keep people away, spilled resin can be a slipping hazard, wear gloves and safety glasses to minimize skin or eye contact.
6B: Incompatible Chemicals	Strong oxidants can create risk of combustion products similar to burning, exposure to strong acids and strong bases can cause a rapid temperature increase.
6C: Environmental Precautions	Keep out of public sewers and waterways.
6D: Containment Materials	Use plastic or paper containers, unlined metal containers not recommended.
6E: Methods of Clean-up	Sweep up material and transfer to containers.

SECTION 7: Handling and Storage	
7A: Handling	Avoid prolonged skin contact. Avoid contact with salts or with salty water to prevent premature exhaustion of the resin. Keep resin moist and avoid allowing resin to completely dry.
7B: Storage	Store in a cool dry place (0° to 45° C) in the original shipping container. This product is thermally sensitive and will have reduced shelf life if subjected to extended periods of time at temperatures exceeding 50° C. Although freezing does not usually damage ion exchange resins, avoid repeated freeze thaw cycles.
7A: TSCA considerations	Ion exchange resins should be listed on the TSCA Inventory in compliance with State and Federal Regulations.

SECTION 8: Exposure Controls/Personal Protection	
8A: Personal Precautions	None noted.
8B: Incompatible Chemicals	Provide adequate ventilation.
8C: Personal Protection Measures	Eye Protection- Safety glasses or goggles.
	Respiratory Protection - Not required for normal use.
	Protective Gloves - Not required for limited exposure but
	recommended for extended contact.



SECTION 9: Physical and Chemical Properties	
Appearance	Mixed Bed-Solid beads approx 0.6 mm diameter
	Carbon-Irregular black granular pieces.
	Mixed Bed-Flammable above 500° C
Flammability or explosive limits	Carbon-Flammable above 220° C
Odor	None
Physical State	Solid
Vapor pressure	N/A
Odor threshold	N/A
Vapor density	N/A
	Mixed Bed-Acidic or basic when mixed with water
pH	Carbon- Near neutral (6 to 8 typical)
Deletive deneity	Mixed Bed-Approx 700 grams/Liter
Relative density	Carbon-Approx 400 grams/Liter
Melting point/freezing point	Mixed Bed-Does not melt, freezes at approx. 0 C
Metung point/freezing point	Carbon-Does not melt or freeze.
Solubility	Insoluble in water and most solvents
Boiling point	Does not boil
	Mlxed Bed-Approx 500° C
Flash point	Carbon- >220° C
Evaporation rate	Does not evaporate
Partition Coefficient (n-octonol/water)	N/A
A	Mixed Bed- Approx 500° C
Auto-ignition temperature	Carbon- >220° C
Decomposition temperature	Mixed Bed- Above 230° C
	Carbon- Above 220° C
Viscosity	N/A



SECTION 10: Stability and Reactivity	
10A: Stability	Stable under normal conditions.
10B: Conditions to Avoid	Heat, exposure to strong oxidants. Wet carbon adsorbs oxygen from air. Contact with strong oxidizing agents can cause rapid combustion.
10C: Hazardous by-products	Organic sulfonates, amines, charred polystyrene, aromatic acids and hydrocarbons, organic amines, nitrogen oxides, carbon oxides, chlorinated hydrocarbons.
10D: Incompatible materials	Strong oxidizing agents (such as HNO ₃), strong bases (such as NaOH), strong acids (such as HCl and H ₂ SO ₄)
10E: Combustion Products	Does not occur

SECTION 11: Toxicological Information		
11A: Likely Routes of Exposure	Oral, skin or eye contact.	
11B: Effects of exposure	Delayed - None known. Immediate (acute) - Rash or burn caused by acidity or causticity. Chronic - None known.	
11C: Toxicity Measures	Skin Adsorption - Unlikely Ingestion - Oral toxicity believed to be low but no LD50 has been established. Inhalation - Unknown, vapors are very unlikely due to physical properties (insoluble solid).	
11D: Toxicity Symptoms	Skin Adsorption - Rash or burn. Ingestion - Indigestion or general malaise. Inhalation - Unknown.	
11E: Carcinogenicity	None known	

SECTION 12: Ecological information		
12A: Eco toxicity	Not harmful to plant or animal life.	
12B: Mobility	Insoluble, acidity or causticity may escape if wet.	
12C: Biodegradability	Not biodegradable.	
12D: Bioaccumulation	Insignificant.	
12E: Other adverse effects	Not Harmful to the environment.	



Revision 1.0 © 2020 ResinTech, Inc.

SECTION 13: Disposal Considerations		
13A: General considerations	Material is non-hazardous.	
13B: Disposal Containers	Most plastic and paper containers are suitable. Avoid use of unlined metal containers.	
13C: Disposal methods	No specific method necessary.	
13D: Sewage Disposal	Not recommended	
13E: Precautions for incineration	May release acids and toxic vapors when burned.	
13F: Precautions for landfills	pH of spent resin may be high. Resins used to remove hazardous materials may then become hazardous mixtures	

SECTION 14: Transportation Information		
14A: Transportation Class	Not classified as a dangerous good for transport by land, sea, or air.	
14B: TDG	Not regulated.	
14C: IATA	Not regulated.	
14D: DOT (49 CFR 172.101)	Not regulated.	

SECTION 15: Regulatory Information		
15A: CERCLA	Not regulated	
15B: SARA Title III	Not regulated	
15C: Clean Air act	Not regulated	
15D: Clean Water Act	Not regulated	
15E: TSCA	Not regulated	
15F: Canadian Regulations	WHMIS - Not a controlled product	
	TDG - Not regulated	
15G: Mexican Regulations	Not Dangerous	

SECTION 16: Other Information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features. Regulatory requirements are subject to change and may differ from one location to another. It is the buyer's responsibility to ensure that their activities comply with federal, state, and local laws.

16A: Date of Revision	1 January 2021



Revision 1.0 © 2020 ResinTech, Inc.