

ARIES

SLOW MELT PHOSPHATE

PRO SERIES, SINGLE-BED, DROP-IN CARTRIDGE

**SCALE & CORROSION INHIBITOR
IRON, MANGANESE, &
CALCIUM SEQUESTRATION
RUST INHIBITOR**

Aries phosphate cartridges contains food grade, slow-melt polyphosphate crystals that dissolve in water to inhibit accumulation of scale and rust. This filter is used primarily where scale, corrosion and increased amounts of iron are present in the water source. Phosphate cartridges are also available in combination with coconut shell GAC for added taste and odor improvement. Sized to fit standard slimline and big blue housings.



HIGHLIGHTS

- Fits Standard Residential & Industrial Size Housing
- Oversized Cartridge for Maximum Media Fill
- Lot numbered
- Made in the USA

APPLICATIONS

- Residential POE
- Post RO
- Food, Beverage, & Ice
- Sprayers

MEDIA

- Slow Melt Phosphate Crystals (50%)

CERTIFICATIONS

- WQA Gold Seal
- California Prop. 65 Compliant

SPECIFICATIONS

- Nominal Rating of 25µ
- Max Pressure of 125 psi (861.85 kpa)
- Max Temperature 100 °F (37.8 °C)

DIMENSIONS	SERVICE FLOW	MAX FLOW	CAPACITY	PART NUMBER
2.5 x 10 in. (Slim Line)	1 gpm (3.79 lpm)	-	30,000 ppm	AF-10-3323
2.5 x 10 in. (Slim Line)	1 gpm (3.79 lpm)	-	40,000 ppm	AF-10-3328
2.5 x 10 in. (Slim Line)	1 gpm (3.79 lpm)	-	50,000 ppm	AF-10-3324
2.5 x 10 in. (Slim Line)	1 gpm (3.79 lpm)	-	60,000 ppm	AF-10-3321
2.5 x 20 in. (Slim Line)	2 gpm (7.57 lpm)	-	80,000 ppm	AF-20-3322
4.5 x 10 in. (Super Blue)	3 gpm (11.36 lpm)	-	120,000 ppm	AF-10-3326-BB
4.5 x 20 in. (Super Blue)	5 gpm (18.93 lpm)	-	200,000 ppm	AF-20-3327-BB



COMPONENT

Filter cartridge Certified to NSF/ANSI Standard 42 and NSF/ANSI Standard 61 for material requirement(s) only. Filter cartridge Certified to NSF/ANSI Standard 372 for low lead compliance.

Revision 1.0

© 2020 ResinTech, Inc.

