URANIUM REMOVAL

PRO SERIES, SINGLE-BED, DROP-IN CARTRIDGE

URANIUM REMOVAL TRACE CONTAMINANT REMOVAL

Aries Drop-In Cartridge containing ResinTech SIR-1200 media for the selective removal of Uranium and other trace contaminants.

APPLICATIONS

- POU Drinking Water
- Post RO
- Food and Bev
- Light Commercial

MEDIA

• ResinTech® SIR-1200 (100%)



HIGHLIGHTS

- Resintech[®] SIR-1200
- Fits Standard Residential & Industrial Size Housing
- Oversized Cartridge for Maximum Media Fill
- Lot numbered
- Made in the USA

SPECIFICATIONS

- Nominal Rating of 25µ
- Max Pressure of 125 psi (861.85 kpa)
- Max Temperature 100°F (37.8 °C)

| DIMENSIONS | SERVICE FLOW | MAX FLOW | CAPACITY | PART NUMBER |
|---------------------------|--------------------|--------------------|--------------|---------------|
| 2.5 x 10 in. (Slim Line) | .25 gpm (0.95 lpm) | .50 gpm (1.89 lpm) | 850 Grains | AF-10-3640 |
| 2.5 x 20 in. (Slim Line) | .50 gpm (1.89 lpm) | 1.0 gpm (3.79 lpm) | 1,500 Grains | AF-20-3640 |
| 4.5 x 10 in. (Super Blue) | .75 gpm (2.84 lpm) | 1.0 gpm (3.79 lpm) | 1,500 Grains | AF-10-3640-BB |
| 4.5 x 20 in. (Super Blue) | 1.0 gpm (3.79 lpm) | 2.0 gpm (7.57 lpm) | 4,400 Grains | AF-20-3640-BB |



Filter cartridge Certified to NSF/ANSI Standard 42 and NSF/ANSI Standard 61 for material requirement(s) only. Filter cartridge Certified to NSF/ANSI Standard 372 for low lead compliance.

Revision 1.0 © 2020 ResinTech, Inc.

COMPONENT

