

## ARIES CALCOR pH NEUTRALIZATION

INLINE SERIES, SINGLE BED CARTRIDGE

PH NEUTRALIZATION  
MINERALIZATION  
CORROSION CONTROL

pH is an indicator of the acid or alkaline condition of water. The pH scale ranges from 0-14; 7 indicates the theoretical neutral point. Neutralization cartridges act on acidic waters by slowly dissolving the calcium carbonate and magnesium oxide media as the water flows through the filter, raising the pH of the water and increasing the alkalinity. This eliminates the effects of corrosive water and can help to prevent corrosion of piping and fixtures.

Aries pH Neutralization cartridges contain a unique blend of Calcite® and Corosex®. The unique combination of media ensure pH correction over a wider range thereby ensuring a more consistently balanced effluent thereby lessening the effects of acidic water and preventing corrosion of piping and fixtures without the negative impact of over correction. Available with Quick Connect connectors in 6" and 12" lengths. Aries Inline filters cartridges are designed for low-flow, point-of-use filtration.



### HIGHLIGHTS

- Controls pH Corrosion
- Allows Mineralization
- Calcor pH Neutralization Media
- Lot Control Traceability
- Quality Produced & Made in the USA
- WQA Gold Seal Certified

### APPLICATIONS

- Post RO
- Water Coolers
- Food and Beverage
- Water and Ice


### SPECIFICATIONS

- Nominal Rating of 25µ
- Max Pressure of 125 psi (850 kPa)
- Max Temperature 100°F (38 °C)



DIMENSIONS	SERVICE FLOW		CAPACITY*		PART NUMBER
	gpm	lpm	gal	L	
6 x 2 in. (Quick Connect)	0.2	0.8	2100	7900	<b>IFB-06-3232-QC</b>
12 x 2 in. (Quick Connect)	0.4	1.5	4200	15900	<b>IFB-12-3232-QC</b>

\*Throughput is dependent upon water chemistry. Results may vary.



### COMPONENTS

- End Caps - ABS
- Pads - PET
- Body - ABS
- Media - Calcite® and Corosex®



**WE ARE PROUD TO BE  
ISO 9001 : 2015 CERTIFIED**

**IMPORTANT NOTICE TO USER:** The following is made in lieu of all other warranties expressed or implied. Manufacturer's and Seller's only obligation shall be to issue credit against the purchase or replacement of the equipment proved to be defective in material or workmanship. Neither Manufacturer nor Seller shall be liable for any injury, loss or damage, direct or indirect, special or consequential, arising out of the use of, misuse, or the inability to use such product. The information contained herein is based on technical data and tests which we believe to be reliable and is intended for use by persons having technical skill at their discretion and risk. Since conditions of use are outside ResinTech's control, we can assume no liability whatsoever for results obtained or damages incurred through the application of the data presented. This information is not intended as a license to operate under, or a recommendation to infringe upon, any patent of ResinTech's or others covering any material or use. The foregoing may not be altered except by written agreement signed by officers of the manufacturer.