## PRODUCT SPECIFICATION SHEET

## SBG1P-OH-ULTRA

STRONG BASE ANION

ULTRAPURE GRADE
TYPE I ANION
POLYSTYRENIC POROUS GEL
HYDROXIDE FORM

ResinTech SBG1P-OH-ULTRA is a type 1 porous gel strong base anion resin in hydroxide form. The ULTRA grade has been functionally tested to produce > 18 megohm resistivity and under 2 ppb of TOC (when mixed with ULTRA grade cation resin). SBG1P-OH-ULTRA is intended for use in industrial demineralizing applications such as two beds and mixed beds where a resin that has been tested to confirm high resistivity and the lowest possible TOC is required.

## **APPLICATIONS**

- Demineralization
- Anion Component in Mixed Beds

TYPICAL PROPERTIES & PHYSICAL CHARACTERISTICS	
Polymer Matrix	Styrenic Porous Gel
Ionic Form	Hydroxide
Functional Group	Trimethylamine
Physical Form	Spherical Beads
Particle Size	16 to 50 US Mesh (297 - 1190 μm)
% < 50 mesh (300μm)	< 1%
Minimum Sphericity	93%
Uniformity Coefficient	1.6
Reversible Swelling	OH to CI -20% to -28%
Temp Limit	140°F (60°C)
Capacity (meq/mL)	1.05
Shipping Weight	41 - 43 lbs/ft³ (657 - 689 g/L)
Color	Yellow to Orange
Regenerability	Yes

## **PACKAGING OPTIONS**

- 1 ft³ bags
- 1 ft<sup>3</sup> boxes
- 1 ft<sup>3</sup> drums
- 7 ft<sup>3</sup> drums
- 42 ft<sup>3</sup> supersacks



